

## B I O H y d r a u l i c O i l 3 2 / 4 6 / 6 8

### HYDRAULIC OIL – HETG (Specification: ISO 15380)

#### Description

**LUBECO™ BIO Hydraulic Oils** are readily biodegradable rapeseed oil based hydraulic lubricants offering an excellent level of lubrication and an improved operating temperature range. Developed to replace the usual mineral oil based hydraulic lubricants to reduce an environmental footprint.

#### Areas of Application

Designed for the lubrication of hydrostatic and hydrodynamic machine mechanisms, particularly suitable for lubricating of hydraulic quick valves in power plants. Produced at a range of viscosity classes ISO VG 32/46/68.

#### Characteristic features

- Improved thermal oxidation stability;
- Great friction and wear test results;
- Exceptional cold exposure properties;
- Excellent lubrication;
- Easily biodegradable;
- Improved anti-rust and anti-corrosion protection;
- Made from renewable resources;
- Non-toxic

#### TYPICAL CHARACTERISTICS

PARAMETER	UNIT	TEST METHOD	ISO VG 32	ISO VG 46	ISO VG 68
Density at 15 °C	kg/m <sup>3</sup>	ISO 12185	912	917	920
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	32	46	68
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	7,2	9,7	13,4
Viscosity Index			200	203	203
Pour point	°C	ASTM D97	-32	-34	-35
Flash point, COC	°C	ASTM D92	>250	>250	>250
Biodegradability (within 21 days)	%	CEC-L-33-A-93	>90	>90	>90

Issue Date: 7/3/2016

