

Technical Data sheet

BIO ROCK DRILL

Biodegradable Rock Drill Lubricant

Description

BIO ROCK DRILL is a high performance, vegetable oil based, readily biodegradable drilling lubricant. **BIO ROCK DRILL** contains specially selected EP/Extreme Pressure and AW/Anti-Wear additives and naturally present extremely high Viscosity Index for superior level of lubricity and improved anti-corrosion & anti-wear protection. **BIO ROCK DRILL** was developed to replace the usual mineral oil based rock drill lubricants in order to provide a greater performance and reduce environmental footprint.

Areas of Application

BIO ROCK DRILL is designed lubricant for all types of rock drilling applications in mining, quarrying, constructions, road works, tunnelling and excavations. **BIO ROCK DRILL** is particularly recomended for use in environmentally sensitive areas to minimise contamination of surface and groundwater.

Characteristic features

- Excellent lubricating properties far superior than that of mineral oils
- Naturally greater adhesion than mineral oils
- High oil film strength
- Improved anti-corrosion & anti-wear protection
- Increased overall system efficiency
- Lower lubricant usage
- Positive impact on CO₂ emissions
- Readily biodegradable Over 98% Biodegradability within 21 days

TYPICAL CHARACTERISTICS

| PARAMETER | UNIT | TEST METHOD | BRD 40 | BRD 100 |
|-----------------------------------|-------------------|----------------|----------|----------|
| Density at 15 °C | kg/m ³ | ISO 12185 | 912 | 935 |
| Kinematic Viscosity at 40°C | mm²/s | ASTM D445 | 40 | 100 |
| Kinematic Viscosity at 100°C | mm²/s | ASTM D445 | 8.6 | 18.1 |
| Viscosity Index (VI) | | | >200 | >200 |
| Pour point | °C | ASTM D97 | <-30 | <-30 |
| Flash point, COC | °C | ASTM D92 | >270 | >250 |
| Steel corrosion at 100°C/3h | | | negative | negative |
| Biodegradability (within 21 days) | % | OECD 301B | >98 | >98 |

Issue Date: 20/12/2016

Pacific Bio Lubricants Limited

11H Piermark Dr., North Harbour Auckland 0632, New Zealand

Postal: PO Box 35085, Auckland 0753

Sales and Technical Support

Phone: +64 9 973 4390 NZ Freephone: 0800 582 326 Email: info@lubeco.co.nz

