

Technical Data sheet

ECO 4T - SA<u>E 30</u>

Full synthetic 4-Stroke Engine Oil

Description

ECO 4T is a premium quality, fully synthetic four-stroke engine oil for high performing engines of small gardening and agricultural equipment requiring SAE30 oil specification. **ECO 4T** contains modern enhancing agents (oxidation and corrosion inhibitors, detergent-dispersant additives) and offers excellent lubrication properties as well as improved engine wear protection. **ECO 4T** is an environmentally friendly alternative to the usual petroleum based products.

Industry Performance Standards

- SAE 30
- API SJ/CF

Areas of Application

ECO 4T is specifically designed for lubrication of 4-Stroke petrol and diesel engines, high-speed small gardening, agricultural and municipal equipment (lawn mowers, ride-on mowers, small tractors, snow blowers, generators, motor pumps, etc) requiring the use of SAE 30 oil grade.

Characteristic features

- Excellent lubrication to all moving parts of highly stressed modern four-stroke engines;
- Improved performance and engine wear protection;
- Easy start at low temperatures;
- Inhibits high-temperature deposits and low-temperature sludge;
- Protection against rust and corrosion even during shutdown period;
- Extra cleanliness of internal engine parts;
- Made from renewable materials, environmentally friendly

PHYSICAL PROPERTIES

PARAMETER	UNIT	TEST METHOD	Typical Value
Kinematic Viscosity at 100°C	mm²/s	EN ISO 3104	11,2
Viscosity Index	1	ISO 2909	150
Evaporation Test, Noack	% vol.	DIN 51 581	7
Pour point	°C	ISO 3016	-35
Flash point, COC	°C	EN ISO 2592	220
TBN	mg KOH/g	ISO 3771	8

Issue Date: 15/5/2016

Pacific Bio Lubricants Limited

11H Piermark Dr., North Harbour Auckland 0632, New Zealand Postal: PO Box 35085, Auckland 0753 **Sales and Technical Support**

Phone: +64 9 973 4390 NZ Freephone: 0800 582 326 Email: info@lubeco.co.nz

